

Page 1 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.02.2018 / 0005
Replacing version dated / version: 12.04.2017 / 0004
Valid from: 12.02.2018
PDF print date: 13.02.2018
26002 TESLANOL D Druck-Gas-Spray 200 ml
26003 TESLANOL D Druck-Gas-Spray 400 ml

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

26002 TESLANOL D Druck-Gas-Spray 200 ml
26003 TESLANOL D Druck-Gas-Spray 400 ml

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

No information available at present.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

Wentronic GmbH, Pillmannstraße 12, 38112 Braunschweig, Germany
Phone:+49 (0)531 2 10 58 - 43, Fax:+49 (0)531 2 10 58 - 743
www.wentronic.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WEC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.
P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

---	---
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	---
content %	---
Classification according to Regulation (EC) 1272/2008 (CLP)	---

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Normally not irritating to skin.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Medical attention recommended.

4.2 Most important symptoms and effects, both acute and delayed

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

Antidote:

None known

SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.02.2018 / 0005

Replacing version dated / version: 12.04.2017 / 0004

Valid from: 12.02.2018

PDF print date: 13.02.2018

26002 TESLANOL D Druck-Gas-Spray 200 ml

26003 TESLANOL D Druck-Gas-Spray 400 ml

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Allow to evaporate.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

If applicable, suction measures at the workstation or on the processing machine necessary.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.
Do not store with flammable or self-igniting materials.
Observe special storage conditions.
Observe special regulations for aerosols!
Store in a dry place.
Store cool.
Keep protected from direct sunlight and temperatures over 50°C.
Only store at temperatures from 15°C to 35°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

(GB) Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
BMGV: ---	Other information: ---	
(GB) Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
BMGV: ---	Other information: ---	
(GB) Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---	Other information: ---	

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. BS EN 14042.
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Normally not necessary.

Skin protection - Hand protection:
Normally not necessary.

Skin protection - Other:

Usual protective working garments

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter AX (EN 14387), code colour brown.

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: gaseous.
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,5 Vol-% (20°C, 4,5 - 6,5 bar)
Upper explosive limit:	10,9 Vol-% (20°C, 4,5 - 6,5 bar)
Vapour pressure:	4,5-6,5 bar (20°C)
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,56 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	365 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Possible build up of explosive/highly flammable vapour/air mixture. Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.02.2018 / 0005

Replacing version dated / version: 12.04.2017 / 0004

Valid from: 12.02.2018

PDF print date: 13.02.2018

26002 TESLANOL D Druck-Gas-Spray 200 ml

26003 TESLANOL D Druck-Gas-Spray 400 ml

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Possible build up of explosive/highly flammable vapour/air mixture.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

26002 TESLANOL D Druck-Gas-Spray 200 ml 26003 TESLANOL D Druck-Gas-Spray 400 ml						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
---------	--	--	--	--	--	--

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

26002 TESLANOL D Druck-Gas-Spray 200 ml							
26003 TESLANOL D Druck-Gas-Spray 400 ml							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Butane							
---------------	--	--	--	--	--	--	--

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number:

1950

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.02.2018 / 0005

Replacing version dated / version: 12.04.2017 / 0004

Valid from: 12.02.2018

PDF print date: 13.02.2018

26002 TESLANOL D Druck-Gas-Spray 200 ml

26003 TESLANOL D Druck-Gas-Spray 400 ml

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

2.1



14.4. Packing group:

-

Classification code:

5F

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1



14.4. Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):

2.1



14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Page 10 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.02.2018 / 0005
 Replacing version dated / version: 12.04.2017 / 0004
 Valid from: 12.02.2018
 PDF print date: 13.02.2018
 26002 TESLANOL D Druck-Gas-Spray 200 ml
 26003 TESLANOL D Druck-Gas-Spray 400 ml

Directive 2010/75/EU (VOC): 100 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 4, 9, 11, 12, 15
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Aerosol — Aerosols

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.02.2018 / 0005

Replacing version dated / version: 12.04.2017 / 0004

Valid from: 12.02.2018

PDF print date: 13.02.2018

26002 TESLANOL D Druck-Gas-Spray 200 ml

26003 TESLANOL D Druck-Gas-Spray 400 ml

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.